

# UltraTape & Labels

Adhesive Tape & Labels for Critical Environments

## UltraLabel Pro Product Comparison



**ULP610**



**ULP300**



**ULP200**

### Hardware Specifications

<b>Resolution</b>	300 dpi (12 dots/mm)	600 dpi (24 dots/mm)	203 dpi (8 dots/mm)
<b>Print Method</b>	Direct thermal/Thermal transfer	Direct thermal/Thermal transfer	Direct thermal/Thermal transfer
<b>Display</b>	Color LCD with buttons LED with buttons	Color LCD with buttons	Color LCD with buttons LED with buttons
<b>Hardwire Connectivity</b>	Ethernet Parallel port Serial RS-232 USB USB Host	Ethernet Parallel port Serial RS-232 USB USB Host	Ethernet Parallel port Serial RS-232 USB USB Host
<b>Wireless Connectivity</b>	Bluetooth MFi Wi-Fi with Bluetooth	Bluetooth MFi Wi-Fi with Bluetooth	Bluetooth MFi Wi-Fi with Bluetooth
<b>Enterprise Printer Management</b>	TSC Console SOTI Connect (license required)	TSC Console SOTI Connect (license required)	TSC Console SOTI Connect (license required)
<b>Type</b>	Desktop	Desktop	Desktop
<b>Max. Print Speed</b>	Up to 6 ips (152 mm/s)	Up to 4 ips (102 mm/s)	Up to 8 ips (203 mm/s)
<b>Max. Print Width</b>	4.17" (106 mm)	4.17" (106 mm)	4.25" (108 mm)
<b>Max. Print Length</b>	450" (11,430 mm)	100" (2,540 mm)	1,000" (25,400 mm)

<b>RAM</b>	128 MB SDRAM	128 MB SDRAM	128 MB SDRAM
<b>Flash</b>	128 MB	128 MB	128 MB
<b>Expandable Flash</b>	microSD card reader; up to 32 GB	microSD card reader; up to 32 GB	microSD card reader; up to 32 GB
<b>Keyboard</b>	Standalone keyboard	Standalone keyboard	Standalone keyboard
<b>Optional Cutter</b>	Regular guillotine cutter (full-cut)	Regular guillotine cutter (full-cut)	Regular guillotine cutter (full-cut)

## Media Specifications

<b>Internal Label Capacity</b>	5" (127 mm) OD	5" (127 mm) OD	5" (127 mm) OD
<b>Max. Media Width</b>	0.75" - 4.4" (19 -112 mm)	0.75" - 4.4" (19 -112 mm)	0.75" - 4.4" (19 -112 mm)
<b>Media Type</b>	Continuous; Die-Cut; Black Mark; Fan-Fold; Notch (Outside Wound)	Continuous; Die-Cut; Black Mark; Fan-Fold; Notch (Outside Wound)	Continuous; Die-Cut; Black Mark; Fan-Fold; Notch (Outside Wound)
<b>Max. Ribbon Length</b>	300 Meters	300 Meters	300 Meters
<b>Ribbon Width</b>	1.6" - 4.3" (40 - 110 mm)	1.6" - 4.3" (40 - 110 mm)	1.6" - 4.3" (40 - 110 mm)
<b>Media Core Diameter</b>	1" - 1.5" (25.4 - 38 mm)	1" - 1.5" (25.4 - 38 mm)	1" - 1.5" (25.4 - 38 mm)
<b>Construction</b>	Clamshell with double-walled plastic	Clamshell with double-walled plastic	Clamshell with double-walled plastic
<b>Programming Languages</b>	TSPL-EZD	TSPL-EZD	TSPL-EZD